

# OCTOPUS

## SWIVEL OCTOPUS

Item OC8X

- Smooth action 180 degree swivel
- Extended exhaust tee
- Downstream demand valve
- Lightweight & compact
- High grade chromed brass
- Long bite mouthpiece
- 36" low pressure hose



## UNITE OCTOPUS

Item OC6X

- Integrates Power Inflator with a 2nd stage
  - eliminates one hose
- Flat & low drag design
- Perfect for any dive position
- Compact & lightweight
- High impact plastic
- High grade chromed brass
- 26" low pressure hose



## OCTOPUS

Item OC4XYL Adjustable

Item OC3XYL Non-Adjustable

- Reliable, safe design
- Outstanding breathing performance
- 36" low pressure hose
- Repair kit available



OC4XYL



OC3XYL

# TANK VALVE / MANIFOLD

## MANIFOLD

Item TK10

- Yoke valves TK-03 (left hand) TK-08 (right hand)
- 225 bar
- Chromium plated brass finish
- Valve thread 3/4" - 14 NPS inlet
- Service pressure: 3000 psi
- Burst pressure: 3500-4000 psi
- Double O-ring seals on each end of crossbar=TK-07
- Center line distance: 171 mm/ 185mm/ 213mm



TK08

TK07

TK03

## TANK PRO VALVE

Item TK02

- Yoke/Din conversion
- Chromium plated brass
- 3/4" - 14 NPS inlet
- Nitrox compatible
- Service pressure: 3000 psi
- Burst pressure: 3500 ~ 4000 psi (200 bar)



## DUAL REGULATOR ADAPTER

Item TK05

**NEW!**

- Yoke Version
- Can be used with Yoke or Din adapters
- Compatible with TK-A5 and TK-A6



## DIN ADAPTER

Item TK-A6

**NEW!**

- Din adapter
- Compatible with TK-05 and TK-06
- 300 bar



## TANK K VALVE

Item TK01

- Standard yoke outlet
- Chromium plated brass
- 3/4" - 14 NPS inlet
- Nitrox compatible
- Service pressure: 3000 psi
- Burst pressure: 3500 ~ 4000 psi (240 bar)



## DUAL REGULATOR ADAPTER

Item TK06

**NEW!**

- Din Version
- Can be used with Yoke or Din adapters
- Compatible with TK-A5 and TK-A6



## YOKE ADAPTER

Item TK-A5

**NEW!**

- Yoke adapter
- Compatible with TK-05 and TK-06

